

# POWERING THE GROWTH JOURNEY OF THE NATION

**CPCB IV+** Range - 5 kVA - 320 kVA



**Best-in-class  
Fuel Efficiency**



**Small  
Footprint**



**Excellent Block  
Loading Capacity**



**Lowest Cost of  
Ownership**



**Widest Sales &  
Service Network**

# 5 kVA to 320 kVA

## TECHNICAL SPECIFICATIONS

Genset Rating (kVA)	Power Rating (kWe)	Engine Model	Rated Power Output# (BHP)	Genset Dimension (LxWxH) (mm) Approx.	Fuel Tank Capacity (lit)
5	4	KD15-441GSI4	8.2	1050 X 600 X 745	15
10	8	M2155G1	16.3	1750 X 900 X 1250	55
*15	12	M2155G2	18.3	1750 X 900 X 1250	55
15	12	M3205G1	22.7	1990 X 900 X 1330	75
*20	16	M3205G2	25.2	1990 X 900 X 1330	75
*25	20	M3205G3	30.5	1990 X 900 X 1330	75
25	20	M3205G4	35.1	1990 X 900 X 1330	75
30	24	M3205G5	40.0	2075 X 980 X 1330	115
*35	28	M3205G5	40.0	2075 X 980 X 1330	115
40	32	M4275G1	51.8	2325 X 980 X 1330	115
*45	36	M4275G1	51.8	2325 X 980 X 1330	115
50	40	V4355G1	65.4	2400 X 1130 X 1575	156
58.5	46.8	V4355G2	75.5	2400 X 1130 X 1575	156
82.5	66	V4355G4	101.3	3190X 1225 X 1575	169
100	80	H4485G2	126	3180 X 1350 X 1700	250
125	100	H4485G1	156	3180 X 1350 X 1700	250
160	128	H6725G2	199	4200 X 1400 X 1745	388
180	144	H4485G2	223	4200 X 1400 X 1745	388
200	160	H6725G4	247	4200 X 1400 X 1745	388
250	200	H6935G1	310	4400 X 1600 X 1850	425
320	256	H6935G2	390	4750 X 1600 X 2000	570

- Above specifications are subject to change without prior notice due to continuous product improvements.
- All engines & alternators conform to respective IS standards
- All the genset specifications conform to ISO 8528 standard
- All specifications are at Standard NTP operating conditions
- Height without Silencer
- Fuel - High Speed Diesel (HSD IS 1460:2005)
- \*Represent the Standby Ratings
- Considering 0.89 Specific Gravity of Oil Engine Power will have + 5% Tolerance



**Mahindra & Mahindra Ltd.,**  
 Mahindra Powerol  
 MHEL, 1st Floor, Gate No. 12, A-1/1,  
 Talawade Chakan Rd, Chakan Industrial Area,  
 Phase-IV, Nigoje, Maharashtra, 410501.

Local Contact

